

Deutscher Verein des Gas- und Wasserfaches e.V.



www.dvgw-regelwerk.de

Technical Rule — Standard **DVGW G 415** September 2015

Design, Construction and Operation of Biogas Pipework with an Operating Pressure up to and including 5 bar

The DVGW is the technical and scientific association of gas and water engineers and comprises approximately 14,000 members. For more than 150 years, the DVGW has been setting the technical standards for the safe, secure and reliable supply of gas and water, actively initiating the exchange of ideas and information in the gas and water sectors and encouraging and promoting on-going progress in the sectors through practical guidance.

The DVGW is an independent non-profit organisation free from economic lobbyism and political influence.

The DVGW Set of Rules is a key instrument for the DVGW to meet its statutable purpose and accomplish its tasks. The DVGW Set of Rules notably defines, on the basis of statutory regulations, the requirements on technical safety, hygiene, environmental protection, fitness for use and consumer protection and organisation for the supply and use of gas and water. The DVGW Set of Rules ensures that the DVGW complies with the statutory principle of self-responsibility of the utilities, for the benefit of technical safety and hygiene as well as environmental and consumer protection.

Note for users

The DVGW Set of Rules rests on the following principles:

- The DVGW Set of Rules has been elaborated in an honorary capacity in accordance with the applicable principles (DVGW Constitution, Rules of Procedure GW 100). On the basis of jurisdiction, both the content and the technical information can be assumed to be correct.
- Everybody can use the DVGW Set of Rules. Duties and obligations may arise from legal or administrative regulations or from a contract or from other legal grounds.
- Nobody can abdicate their responsibility for correct action when applying the DVGW Set of Rules. Anyone applying the DVGW Set of Rules shall ensure its correct application in each concrete case.
- While the DVGW Set of Rules is not the only source of knowledge when looking for professional solutions, it
 does constitute an important source of such knowledge. It cannot however cover all possible special cases
 that may require more comprehensive or restrictive measures.

Warning

This English-language version is an informal translation from the German original. However, only the original German language version has been exclusively authorised by the DVGW and its Technical Bodies. The DVGW reserves the right to revise this version at any time due to possible translation errors.

Anybody is free to use the DVGW system of rules. Users are responsible for the proper use of the DVGW system of rules in each individual case.

ISSN 0176-3490 Price group: 5

© DVGW, Bonn, September 2015

DVGW German Technical and Scientific Association for Gas and Water

Josef-Wirmer-Straße 1-3

D-53123 Bonn

Phone: +49 228 9188-5 Fax: +49 228 9188-990 Email: info@dvgw.de Internet: www.dvgw.de

Reprinting and photomechanical reproduction, also of excerpts, is only permitted with the approval of the DVGW e.V., Bonn.

Distribution: Wirtschafts- und Verlagsgesellschaft Gas und Wasser mbH, Josef-Wirmer-Str. 3, D-53123 Bonn

Phone: +49 228 9191-40 · Fax: +49 228 9191-499 Email: info@wvgw.de · Internet: shop.wvgw.de

Design, Construction and Operation of Biogas Pipework with an Operating Pressure up to and including 5 bar



Contents

Forew	oreword	
1	Scope	7
2	Normative references	7
3	Terms, symbols, units and abbreviations	
3.1	Biogas	9
4	Design	9
4.1	General	9
4.2	Approval / permission procedure	10
4.3	Pipeline routing	10
4.4	Material	10
4.5	Entry into buildings	10
5	Construction	11
5.1	General	11
5.2	Personnel requirements	11
5.2.1	Skilled personnel, qualified persons and experts	11
5.2.2	Pipework contractors	11
5.3	Transport and storage of pipes	11
5.4	Pipe and pipeline component inspection	12
5.5	Depth of cover	12
5.6	Pipe trenches and excavation pits	12
5.7	Pipework connections	12
5.7.1	General	12
5.7.2	Welded joints	12
5.7.3	Compression joints and press-fit assemblies	12
5.7.4	Flanged joints	12
5.8	Pipe bends - elastic bending	12
5.9	Gas pipework installation	13
5.10	Backfilling	13
5.11	Trenchless laying methods	13
5.12	Installation of valves and fittings	13
5.13	Marking	13
6	Pressure test	14
7	Acceptance certificate	14
8	Commissioning	14

9	Operation	14
9.1	General	14
9.2	Personnel requirements	
9.3	Maintenance	15
9.3.1	Condensate trap emptying	15
9.3.2	Pigging of pipeline sections	
9.3.3	Leak testing of connections	15
9.4	Stand-by service	16
10	Documentation	
10.1	Construction	
10.2	Operation	16
Annex	A (informative) – Typical condensate trap	17
Annex	B (informative) – Overview of Set of Rules	18

Foreword

This Standard has been elaborated by the "Biogas Pipework" project group of the Technical Committee on "Gas Distribution". This DVGW Standard can be used as a guideline as it summarises the minimum requirements specified in the DVGW Sets of Rules that shall be observed by design firms, specialist contractors, operators and the involved authorities during the design, construction and operation of gas pipework for the transmission of untreated or partially treated biogas. The clause on "Design" also draws attention to the fact that the pertinent approvals and/or permissions shall be obtained prior to the start of construction of pipework planned to cross e.g. water bodies, roads and railways.

Gases produced by fermentation processes such as e.g. biogases obtained from agriculture that are generally used to meet internal requirements and/or to power decentralised systems such as e.g. combined heat and power plants, are untreated or partially treated biogases that are not considered gases in accordance with DVGW Standard G 260.

Nonetheless, the documents that form part of the DVGW Set of Rules that are referred to in this Standard shall also be applied to pipelines that transmit untreated or partially treated biogas.

This Standard supersedes DVGW Guideline G 415:2011-06.

Amendments

The following amendments have been made in comparison with DVGW Guideline G 415:2011-06:

- Editorial revision a)
- b) Restriction of the scope of application to a maximum admissible operating pressure up to and including 5 bar
- c) Additional notes on how to install valves, fittings and vents and on piggability
- d) Restriction of the scope of application to cover only polyethylene
- Additional notes on how to mark a biogas pipeline on site e)
- Additional notes on occupational safety and hygiene f)
- Additional notes on staff requirements for operation g)

- h) Additional notes on the use of temporary shut-off devices, the emptying of condensate traps and the pigging of pipeline sections
- i) Additional notes on information about pipework

Earlier editions

DVGW G 415 (M):2011-06