



Deutscher Verein des Gas- und Wasserfaches e.V.



www.dvgw-regelwerk.de

Technical Information — Guideline **DVGW G 655 (M)** April 2021

Guideline H2-Readiness Gas Utilisation

Leitfaden H2-Readiness Gasanwendung

H₂ Ready

GAS

The DVGW is the technical and scientific association of gas and water engineers and comprises approximately 14,000 members. For 160 years, the DVGW has been setting the technical standards for the safe, secure and reliable supply of gas and water, actively initiating the exchange of ideas and information in the gas and water sectors and encouraging and promoting on-going progress in the sectors through practical guidance.

The DVGW is an independent non-profit organisation free from economic lobbyism and political influence.

The DVGW Set of Rules is a key instrument for the DVGW to meet its statutable purpose and accomplish its tasks. The DVGW Set of Rules notably defines, on the basis of statutory regulations, the requirements on technical safety, hygiene, environmental protection, fitness for use and consumer protection and organisation for the supply and use of gas and water. The DVGW Set of Rules ensures that the DVGW complies with the statutory principle of self-responsibility of the utilities, for the benefit of technical safety and hygiene as well as environmental and consumer protection.

Note for users

The DVGW Set of Rules rests on the following principles:

- The DVGW Set of Rules has been elaborated in an honorary capacity in accordance with the applicable principles (DVGW Constitution, Rules of Procedure GW 100). On the basis of jurisdiction, both the content and the technical information can be assumed to be correct.
- Everybody can use the DVGW Set of Rules. Duties and obligations may arise from legal or administrative regulations or from a contract or from other legal grounds.
- Nobody can abdicate their responsibility for correct action when applying the DVGW Set of Rules. Anyone applying the DVGW Set of Rules shall ensure its correct application in each concrete case.
- While the DVGW Set of Rules is not the only source of knowledge when looking for professional solutions, it
 does constitute an important source of such knowledge. It cannot however cover all possible special cases
 that may require more comprehensive or restrictive measures.

Warning

This English-language version is an informal translation from the German original. However, only the original German language version has been exclusively authorised by the DVGW and its Technical Bodies. The DVGW reserves the right to revise this version at any time due to possible translation errors.

Anybody is free to use the DVGW system of rules. Users are responsible for the proper use of the DVGW system of rules in each individual case.

ISSN 0176-3490

Price group: 3

© DVGW, Bonn, Juli 2019

DVGW German Technical and Scientific Association for Gas and Water

Josef-Wirmer-Straße 1-3

D-53123 Bonn

Phone: +49 228 9188-5 Fax: +49 228 9188-990 Email: info@dvgw.de Internet: www.dvgw.de

Reprinting and photomechanical reproduction, also of excerpts, is only permitted with the approval of the DVGW e.V., Bonn.

Distribution: Wirtschafts- und Verlagsgesellschaft Gas und Wasser mbH, Josef-Wirmer-Str. 3, D-53123 Bonn

Phone: +49 228 9191-40 · Fax: +49 228 9191-499 Email: info@wvgw.de · Internet: shop.wvgw.de

Art.No.: 312678 G

Guideline H2-Readiness Gas Utilisation



Contents

Preface 5

Intro	Introduction		
1	Scope	9	
2	Normative References	9	
3	Terms, Symbols, Units, and Abbreviations	11	
3.1	Hydrogen-rich Fuel Gases	11	
3.2	Hydrogen	11	
4	Gas Properties	11	
4.1	Natural Gases According to DVGW G 260 (A)	11	
4.2	Natural Gas/Hydrogen Mixtures up to 10 vol % H ₂	11	
4.3	Natural Gas/Hydrogen Mixtures beyond 10 vol % to 20 vol % H ₂	12	
4.4	Hydrogen	12	
5	Requirements for Persons and Companies	13	
6	Requirements for Pipework Components and Materials	13	
6.1	Natural Gas/Hydrogen Mixtures beyond 10 vol % to 20 vol % H ₂	13	
6.2	Hydrogen	14	
7	Requirements for Pipework Installation	14	
7.1	Natural Gas/Hydrogen Mixtures beyond 10 vol % to 20 vol % H ₂	14	
7.2	Hydrogen	14	
8	Pipework Design	14	
8.1	Natural Gas/Hydrogen Mixtures beyond 10 vol % to 20 vol % H ₂	14	
8.2	Hydrogen	15	
9	Gas Appliances	15	
9.1	Natural Gas/Hydrogen Mixtures beyond 10 vol % to 20 vol % H ₂	15	
9.2	Hydrogen	15	

10	Installation of Gas Appliances / Combustion Air Supply / Exhaust Gas Discharge	16
10.1	Natural Gas/Hydrogen Mixtures beyond 10 vol % to 20 vol % H ₂	16
10.2	Hydrogen	16
11	Industrial Gas Applications	16
11.1	Thermoprocessing Equipment	16
11.2	Power Plants	16
11.3	Chemical Applications	17
12	Filling Stations (Fuelling Stations)	17
12.1	CNG Filling Stations	17
12.2	Hydrogen Filling Stations	17
13	Adjustment or Conversion of distributed Gas	17
13.1	Adjustment to Hydrogen-rich Gases	17
13.1.1	Components and Pipework	17
13.1.2	Gas Appliances	18
13.1.3	Industrial Gas Applications	18
13.2	Hydrogen Conversion	18
Annex	A (normative) – Dimensioning Tables for Hydrogen – Domestic Applications <i>mutatis</i>	
	mutandis according to DVGW Code of Practice G 600, DVGW-TRGI	19
Annex	B (normative) – Dimensioning Tables for Industrial Pipework for Hydrogen with an	
	Operating Pressure of up to 100 hPa/mbar (analogous to DVGWCode of Practice G 614-1)	22
	G 014-1)	∠3
Furthe	r Reading	30

Preface

This Guideline was developed by the project group "H₂ Readiness for Gas Installation" within the Technical Committee "Gas Installation" with the involvement of representatives from Technical Committees "Domestic, Commercial, and Industrial Gas Applications", "Components and Auxiliary Materials - Gas", as well as of "Infrastructure Gas Mobility".

According to the German Energy Industry Act ("Energiewirtschaftsgesetz"; EnWG) Article 3 No 10c und No 19a the injection of hydrogen and other renewable gases is permissible. In combination with Article 49 of the Energy Industry Act, the DVGW Sets of Rules and, specifically, the technical rules Code of Practice G 260 "Gas Quality", for domestic installations still G 600 "Technical Rule for Gas Installations" (DVGW TRGI) and G 614-1 "Above-Ground Gas Pipelines on Premises behind Point of Delivery — Design, Construction, Testing and Commissioning" shall be taken into account...

According to DVGW Code of Practice G 262:2011-09 "Usage of Gases from Regenerative Sources in the Supply of the General Public with Gas", the injection of < 10 vol% hydrogen has been admissible. The revision of DVGW G 260:2020-09 (draft) and entailed fusion with DVGW G 262 (A) has laid the basis for the injection of hydrogen of up to 20 vol%. In principle, the injection with such a volume was already possible through applying a corresponding exception in DVGW G 260 (A):2013 Section 4.2.2 "Relative Density" and carrying out pre-acceptance testing in case values fell below the relative density.

To make "pure" hydrogen networks possible, an amendment of the Energy Industry Act is currently being developed which will integrate pure hydrogen networks into the Act. There, the DVGW Sets of Rules are referenced as the generally accepted state-of-art.

This Guideline further expands the DVGW sets of rules for hydrogen-rich natural gas of up to 20 vol% H₂. or hydrogen in the context of a two-step process.

In the first step, "H2 Guidelines" are developed for the fields "gas infrastructure" and "gas utilisation" which describe the protection objectives for hydrogen-rich natural gases and hydrogen that must be adhered to and that supplement the existing sets of rules. The goal is to expand the scope of application of DVGW Sets of Rules to natural gas/hydrogen mixtures or pure hydrogen. The process includes advice and recommended actions that make e.g., the realization of pilot projects or conducting individual certified acceptance tests possible.

In the second step, the respective national and European rulesets are revised and adjusted in detail with consideration towards the results of parallelly occurring F&E activities.

In some sections, only generalized specifications or notes are currently possible. As soon as new state of knowledge exists, these generalized items will be specified with more precision.

This Guideline is a first publication.